

Geotextiles | Erosion Control | Geogrids | Geomembranes

## Carthage %<sup>™</sup> Open Area Monofilament Geotextiles

The <u>Carthage % Open Area Series</u> of woven monofilament geotextiles are made of high-tenacity, polypropylene yarns which are woven into a stable network such that they retain their relative position. The <u>Carthage % Open Area Series</u> of woven monofilament filtration geotextiles is inert to biological degradation and resistant to naturally encountered chemicals, alkalis, and acids.

PROPERTY	METHOD	UNIT	Carthage 6%™ (1)	Carthage 15%™	Carthage 30%™ (1)	Carthage 4%HD™	Carthage 10%HD™	Carthage 12%HD™
Mechanical								
Grab Tensile Strength	ASTM D 4632	lbs	370 x 250	365 x 200	350 x 280	400 x 315	425 x 350	400 x 335
Grab Tensile Elongation		%	15%	24% x 10%	30% x 18%	15%	20%	20 x 13%
Wide Width Tensile	ASTM D 4595	lbs/in	NA	NA	NA	250 x 230	270 x 255	230 x 225
Trapezoidal Tear	ASTM D 4533 ASTM D 6241	lbs	100 x 60	115 x 75	100 x 98	150 x 165	145 x 125	145 x 125
CBR Puncture			950	675	870	1,150	1,340	1,250
Endurance UV Resistance	ASTM D 4355	% @ 500 hrs	90%	90%	90%	90%	90%	90%
Hydraulics/Filtration								
Permittivity	ASTM D 4491	sec <sup>-1</sup>	0.28	2.10	4.0	0.90	0.96	1.50
Water Flow Rate		gpm/ft <sup>2</sup>	18	145	300	70	70	115
Percent Open Area	CW-02215	%	4–6%	10-15%	20-30%	1-4%	6-10%	8-12%
Apparent Opening Size (AOS) <sup>(a)</sup>	ASTM D 4751	US Std Sieve	70	40	30	40	40	30
🗆 Physical	Measured (Typical)	ft 900 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100	6.0 x 300 200 85	12.0 x 300 400 175	12.0 x 300 400 157	15.0 x 300 500 290	12.5 x 300 417 245	12.5 x 300 417 228
Standard Roll Sizes Packaging Weight			12.0 x 300 400 173				15 x 300 500 320	15 x 300 500 325

NOTES: Mullen Burst Strength ASTM D 3786 is no longer recognized by ASTM D35 on Geosynthetics. Puncture Strength ASTM D 4833 is not recognized by AASHTO M 288 and has been replaced with CBR Puncture ASTM D 6241.

a) AOS, typically referred to as a MARV, is actually reported as a MAXIMUM allowable opening when in English US Sieve units; or as the SMALLEST allowable opening when in Metric units (mm).

Unless otherwise stated, all values stated here are Minimum Average Roll Values (MARV).

The properties reported above are effective 01-01-2024 and are subject to change without notice.

<sup>(1)</sup> An independent study – <u>Independent Research on Fabric Clogging</u> – evaluated the hydraulic performance and clogging potential of the four major types of geotextiles including the three highlighted above, and determined that the combined Hydraulic/ Filtration properties of **Percent Open Area (POA)** and **Apparent Opening Size (AOS)**, proved to be the "most critical" in predicting long-term filtration performance. A companion review – <u>Why Percent Open Area?</u> – explains the *Role, Function* and *Importance* of Percent Open Area (a property unique to woven monofilaments) in the mechanics of geotextile filtration. Both papers can be viewed by clicking on their links above, or via the home page of the <u>Monofilament Series</u> of the Carthage Mills website at <u>www.carthagemills.com</u>.

Carthage Mills assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Carthage Mills disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Carthage Mills 4243 Hunt Road Cincinnati, OH 45242 www.carthagemills.com 513-794-1600 TELEPHONE 800-543-4430 TOLL FREE 513-794-3434 FACSIMILE info@carthagemills.com

Since 1958: America's First Geotextile Company