

Geotextiles | Erosion Control | Geogrids | Geomembranes

FX®-300MF

Carthage Mills' FX-300MF is a woven High-Performance geotextile produced from high-tenacity polypropylene yarns. FX-300MF is part of the Carthage $FX^{\textcircled{S}}$ High-Performance Series of woven geotextiles, is inert to biological degradation, and resistant to naturally encountered chemicals, alkalis and acids.

| PROPERTY | TEST METHOD | DATA | |
|---|-----------------------|--|--|
| | | METRIC | ENGLISH |
| Mechanical/Performance/Design | | | |
| Wide Width Tensile Ultimate | ASTM D 4595 | 52.5 x 47.3 kN/m | 3600 x 3240 lbs/ft |
| Wide Width Tensile @ 5% Strain | | 21.9 x 22.8 kN/m | 1500 x 1560 lbs/ft |
| Mechanical/Index Grab Tensile Strength | ASTM D 4632 | 1.780 x 1.335 kN | 400 X 300 lbs |
| Grab Tensile Elongation | N3111 D 1032 | 10% x 6% | |
| Trapezoidal Tear | ASTM D 4533 | 0.601 x 0.556 kN | 135 x 125 lbs |
| CBR Puncture | ASTM D 6241 | 6.453 kN | 1450 lbs |
| Endurance UV Resistance | ASTM D 4355 | 80% @ 500 hrs | |
| Hydraulics/Filtration Permittivity ⁽¹⁾ | | 0.90 sec ⁻¹ | |
| Water Flow Rate ⁽¹⁾ | ASTM D 4491 | 2444 lpm/m ² | 60 gpm/ft ² |
| Apparent Opening Size (AOS) ^(1,2) | ASTM D 4751 | 0.600 mm | 30 US Std. Sieve |
| 🗆 Physical | | | |
| Standard Roll Sizes / Packaging / Weight | Measured (Typical) | 4.57 m x 91.4 m 418 m² 147.41 kg | 15.0 ft x 300 ft 500 yd ² 325 lbs |

NOTES: Mullen Burst Strength ASTM D 3786 is no longer recognized by ASTM D35 on Geosynthetics. Puncture Strength ASTM D 4833 is not recognized by AASHTO M 288 and has been replaced with CBR Puncture ASTM D 6241.

(1) At the time of manufacturing. Handling, storage and shipping may change these properties.

(2) Maximum Average Roll Value

Unless otherwise stated, all values stated here are Minimum Average Roll Values (MARV).

The properties reported above are effective 01-01-2024 and are subject to change without notice.

Carthage Mills assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Carthage Mills disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Carthage Mills 4243 Hunt Road Cincinnati, OH 45242 www.carthagemills.com 513-794-1600 TELEPHONE 800-543-4430 TOLL FREE 513-794-3434 FACSIMILE info@carthagemills.com

Since 1958: America's First Geotextile Company