



■ FX[®]-HSE Series of Nonwoven Geotextiles

Carthage Mills' FX-HSE Series of nonwoven geotextiles is designed specifically for the environmental market, is constructed of 100% polypropylene staple fibers which are formed into a random network, needle-punched and heatset for dimensional stability. The [FX[®]-HSE Series](#) of nonwoven geotextiles delivers high durability; excellent physical and hydraulic properties; is inert to biological degradation; and resistant to naturally encountered chemicals, alkalis, and acids.

The Carthage Mills' FX-HSE Series of environmental nonwoven geotextiles designates "Mass Per Unit Area" or "Weight Per Square Yard" as a true Minimum value.

Note: The listing below is a sampling of available products in this Series environmental geotextiles. For more information and/or a complete listing of all the products in this Series, please call or visit our website.

| PROPERTY | ASTM TEST | UNIT | FX [®] -40HSE | FX-60HSE | FX-80HSE | FX-100HSE | FX-120HSE* | FX-160HSE | FX-600HSE |
|---|-----------|---------------------|--|----------|----------|-----------|------------|-----------|-----------|
| <input type="checkbox"/> Mechanical | | | | | | | | | |
| Grab Tensile Strength | D 4632 | lbs | 105 | 160 | 225 | 270 | 320 | 425 | 170 |
| Grab Tensile Elongation | | % | 50% | 50 | 50 | 50 | 50 | 50 | 50 |
| Trapezoidal Tear | D 4533 | lbs | 45 | 65 | 90 | 100 | 125 | 150 | 70 |
| CBR Puncture | D 6241 | | 305 | 450 | 600 | 725 | 900 | 1200 | 450 |
| <input type="checkbox"/> Endurance | | | | | | | | | |
| UV Resistance | D 4355 | % @ 500 hrs | 70% | 70% | 70 | 70 | 70 | 70 | 80 |
| <input type="checkbox"/> Hydraulics/Filtration | | | | | | | | | |
| Permittivity ⁽¹⁾ | D 4491 | sec ⁻¹ | 2.00 | 1.63 | 1.26 | 0.94 | 0.70 | 0.31 | 1.50 |
| Water Flow Rate ⁽¹⁾ | | gpm/ft ² | 160 | 125 | 100 | 75 | 50 | 45 | 110 |
| Apparent Opening Size (AOS) ⁽¹⁾ | D 4751 | US Std Sieve | 70 | 70 | 80 | 100 | 100 | 100 | 80 |
| <input type="checkbox"/> Physical | | | | | | | | | |
| Mass Per Unit Area (Minimum) | D 5261 | oz/yd ² | 4.0 | 6.0 | 8.0 | 10.0 | 12.0 | 16.0 | 6.0 |
| Thickness (Typical) | D 5199 | mils | 70 | 85 | 100 | 110 | 120 | 140 | 80 |
| Standard Roll Sizes / Packaging / Weight | | | Call for all Roll Sizes, Packaging and Weights | | | | | | |

NOTES: Mullen Burst Strength ASTM D 3786 is no longer recognized by ASTM D35 on Geosynthetics. Puncture Strength ASTM D 4833 is not recognized by AASHTO M 288 and has been replaced with CBR Puncture ASTM D 6241.

⁽¹⁾ At the time of manufacturing. Handling, storage and shipping may change these properties.

■ Unless otherwise stated, all values stated here are Minimum Average Roll Values (MARV); are calculated as the Typical minus two standard deviations; and are based on a 97.7% confidence level.

■ The properties reported above are effective 06-01-24 and subject to change without notice.

*NOTE: Please note that the data for FX-120HSE has not been updated since 2020, and will be updated when possible in 2021

Carthage Mills assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Carthage Mills disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Carthage Mills
4243 Hunt Road
Cincinnati, OH 45242
www.carthagemills.com

513-794-1600 TELEPHONE
800-543-4430 TOLL FREE
513-794-3434 FACSIMILE
info@carthagemills.com

Since 1958: America's *First* Geotextile Company



FX[®]-HSE Series of Nonwoven Geotextiles

Carthage Mills' FX-HSE Series of nonwoven geotextiles is designed specifically for the environmental market, is constructed of 100% polypropylene staple fibers which are formed into a random network, needle-punched and heatset for dimensional stability. The [FX[®]-HSE Series](#) of nonwoven geotextiles delivers high durability; excellent physical and hydraulic properties; is inert to biological degradation; and resistant to naturally encountered chemicals, alkalis, and acids.

The Carthage Mills' FX-HSE Series of environmental nonwoven geotextiles designates "Mass Per Unit Area" or "Weight Per Square Yard" as a true Minimum value.

Note: The listing below is a sampling of available products in this Series environmental geotextiles. For more information and/or a complete listing of all the products in this Series, please call or visit our website.

| PROPERTY | ASTM TEST | UNIT | FX [®] -800HSE | FX-1000HSE | FX-1200HSE | FX-1600HSE | FX-2000HSE | FX-2400HSE | FX-2800HSE | FX-3200HSE |
|---|-----------|---------------------|--|------------|------------|------------|------------|------------|------------|------------|
| <input type="checkbox"/> Mechanical | | | | | | | | | | |
| Grab Tensile Strength | D 4632 | lbs | 230 | 270 | 320 | 425 | 450 | 500 | 725 | 830 |
| Grab Tensile Elongation | | % | 50% | 50 | 50 | 50 | 50 | 50 | 50 | 50 |
| Trapezoidal Tear | D 4533 | lbs | 95 | 105 | 125 | 155 | 175 | 200 | 250 | 300 |
| CBR Puncture | D 6241 | | 675 | 725 | 900 | 1200 | 1310 | 1800 | 2100 | 2287 |
| <input type="checkbox"/> Endurance | | | | | | | | | | |
| UV Resistance | D 4355 | % @ 500 hrs | 80% | 80% | 80 | 80 | 80 | 70 | 70 | 80 |
| <input type="checkbox"/> Hydraulics/Filtration | | | | | | | | | | |
| Permittivity ⁽¹⁾ | D 4491 | sec ⁻¹ | 1.40 | 1.20 | 0.90 | 0.70 | - | - | - | - |
| Water Flow Rate ⁽¹⁾ | | gpm/ft ² | 110 | 85 | 65 | 50 | - | - | - | - |
| Apparent Opening Size (AOS) ⁽¹⁾ | D 4751 | US Std Sieve | 80 | 100 | 100 | 100 | 100 | 100 | 100 | 100 |
| <input type="checkbox"/> Physical | | | | | | | | | | |
| Mass Per Unit Area (Minimum) | D 5261 | oz/yd ² | 8.0 | 10.0 | 12.0 | 16.0 | 20.0 | 24.0 | 28.0 | 32.0 |
| Thickness (Typical) | D 5199 | mils | 90 | 115 | 130 | 175 | 180 | 200 | 275 | 290 |
| Standard Roll Sizes / Packaging / Weight | | | Call for all Roll Sizes, Packaging and Weights | | | | | | | |

NOTES: Mullen Burst Strength ASTM D 3786 is no longer recognized by ASTM D35 on Geosynthetics. Puncture Strength ASTM D 4833 is not recognized by AASHTO M 288 and has been replaced with CBR Puncture ASTM D 6241.

⁽¹⁾ At the time of manufacturing. Handling, storage and shipping may change these properties.

■ Unless otherwise stated, all values stated here are Minimum Average Roll Values (MARV); are calculated as the Typical minus two standard deviations; and are based on a 97.7% confidence level.

■ The properties reported above are effective 06-01-24 and subject to change without notice.

***NOTE:** Please note that the data for FX-120HSE has not been updated since 2020, and will be updated when possible in 2021

Carthage Mills assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Carthage Mills disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Carthage Mills
4243 Hunt Road
Cincinnati, OH 45242
www.carthagemills.com

513-794-1600 TELEPHONE
800-543-4430 TOLL FREE
513-794-3434 FACSIMILE
info@carthagemills.com

Since 1958: America's *First* Geotextile Company