

Geotextiles | Erosion Control | Geogrids | Geomembranes



## LX<sup>™</sup>-SB Spunbond Landscape Fabrics

Carthage Mills' LX-SB Spunbond Line of nonwoven landscape fabrics are polyester (PET) geotextiles. With their high strength to weight ratios, these landscape fabrics provide excellent dimensional stability. The polyester construction of this line is non-biodegradable, is rot and mildew resistant and offer excellent ultraviolet resistance insuring its long life in your project. The Carthage Mills LX-SB Line of spunbond nonwoven landscape fabrics provides excellent separation while allowing for the passage of air, water and fertilizer. These fabrics are ideal to use as a weed block, an underlayment for patio and paver applications, and as a drainage filter fabric.

PROPERTY	TEST METHOD	PRODUCTS		
		LX-SB 20	LX-SB 30	
Weight	ASTM D 3776	2.0 oz/yd²	3.0 oz/yd²	
Grab Tensile (MD x TD)	ASTM D 4632	48.1 x 56.4 lbs 88 x 68.1 lbs		
Grab Elongation	ASTM D 4632	61%	70%	
Trapezoidal Tear	ASTM D 4533	24 lbs	54.4 x 49.4 lbs	
Puncture Resistance	ASTM D 6241	18.2 lbs 30.8 lbs		
Permittivity	ASTM D 4491	3.93 Sec -1	3.43 Sec -1	
Water Flow	ASTM D 4491	293.8 Gal/Min/SF 256.8 Gal/Min/SF		
Apparent Opening Size	ASTM D 4751	50 U.S. Sieve 70 U.S. Sieve		
U.V. Resistance	ASTM D 4355	70% @ 500 hrs 70% @ 500 hrs		

Standard Roll Sizes	Measured (Typical)	3 x 300	4 x 300	6 x 300	12 x 300
Area		900 ft <sup>2</sup>	1200 ft²	1800 ft <sup>2</sup>	3600 ft <sup>2</sup>

- The properties reported above are Typical Values, effective 01-01-2024, and are subject to change without
- notice. Custom roll lengths available upon request

Seller makes no warranty, expressed or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specification stated herein. Any implied warranty of fitness for a particular purpose is expressly excluded, and, to the extent that it is contrary to the foregoing sentence, any implied warranty of merchantability is expressly excluded. Any recommendations made by seller concerning the uses or applications of said product are believed reliable and seller makes no warranty of results to be obtained. If the product does not meet Carthage Mills current published specifications, and the customer gives notice to Carthage Mills before installing the product, then Carthage Mills will replace the product without charge or refund the purchase price.