



## FHWA Specification (Section 714): Geotextile Selection Guide

SPECIFICATIONS	WOVEN		NONWOVEN	
<b>TABLE 714-1:</b> Subsurface Drainage / Separation Stabilization and Geotextile Filter (No Slit Film)				
	Class 1	Class 2	Class 1	Class 2
Type A	Carthage 10% HD	Carthage 4% HD	FX-8oHS	FX-6oHS
Type B	Carthage 10% HD	Carthage 4% HD	FX-8oHS	FX-6oHS
Type C	-	-	FX-8oHS	FX-6oHS
Type D	Carthage 10% HD	Carthage 4% HD	FX-8oHS	FX-6oHS
Type E	-	-	FX-8oHS	FX-6oHS
<b>TABLE 714-2:</b> Paving Geotextiles				
			FX-46AO	
<b>TABLE 714-4:</b> Stabilization Geogrid				
	Biaxial Geogrid GBX-12			
<b>TABLE 714-5:</b> (on 714-6) Reinforcement Geotextile & Geogrid				
Type I	SF35			
Type II	SF35			
Type III	SF55			
Type IV	SF65			
Type V	SF80			
Type VI	SF110			
<b>TABLE 714-7:</b> Geomembrane				
	Textured PVC HDPE or LLDPE		Thickness 28.5-31.5 mils	

- The properties reported above are effective 01-01-19 and are subject to change without notice.

Carthage Mills assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Carthage Mills disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.